

PLC-XU75

XGA Ultraportable Multimedia Projector



ULTRA-COMPACT, FULLY PORTABLE XGA DESIGN

Not much larger than a laptop PC, the PLC-XU75 weighs less than 6.8 pounds and delivers true XGA picture quality in a versatile, go-anywhere system. Also the PLC-XU75 may be ceiling or inverse mounted for enhanced versatility.

F1.65-1.81 ZOOM LENS WITH 1/2X TO 16X DIGITAL ZOOM

Comes with its own 1:1.2 zoom lens, which can throw a crisp, bright 100" diagonal image from a distance of only 11.5'. 1/2X to 16X Digital Zoom helps highlight important program segments.

NEW PROGRESSIVE IC WITH 3-2 AND 2-2 PULLDOWN

SANYO's proprietary progressive integrated circuit significantly improves the appearance of moving images. This IC incorporates 3-2 and 2-2 pull-down technology, which can effectively double the resolution of images from DVD playback.

DUAL D-SUB15 INPUTS

The PLC-XU75 offers excellent flexibility via a pair of D-Sub 15 input terminals. Using an optional adapter cable, it can even accept component video signals. One of the D-Sub 15 terminals can even be switched between input and monitor output for greater programming flexibility.

BLACK BOARD MODE

For more effective presentations in rooms with dark-surfaced walls (i.e.: green boards), the PLC-XU75 projector features BLACK BOARD MODE, which adjusts white balance and gamma correction automatically to project an intelligible image without a screen.

SECURITY FEATURES

PIN code lock provides for the security of the projector settings. The PLC-XU75 projector cannot be operated without a four digit number.

USER-SPECIFIED START-UP SCREEN

To create a smoother, more professional presentation, logo and image files may be captured for display during the projector's countdown sequence at start-up.

VARIABLE AUDIO OUT

This convenient feature on the PLC-XU75 allows the user to control the audio level right from the projector. This centralization of video and audio controls from the projector helps in educational applications by ensuring the technical quality of the presentation and eliminating the fuss of separate outside audio controls.



PRESENTATION TECHNOLOGIES

21605 Plummer Street
Chatsworth, CA 91311
Ph: 888-337-1215 (toll-free)
Fax 818.717.2719
www.sanyolcd.com

Specifications

| | |
|-----------------------------|--|
| Resolution | XGA (1024 x 768) |
| Brightness | 2500 ANSI Lumens |
| Uniformity | 85% (corner to center) |
| LCD Panel System | 0.63" TFT Poly x 3 |
| Number of Pixels | 2,359,296 (786,432 x 3) |
| Contrast Ratio | 450:1 (Lamp Mode "Auto", Image Mode "Dynamic") |
| Image Size (diagonal) | 40" - 300" |
| Aspect Ratio | 4:3 |
| Throw Distance | 4.6' - 41.3' |
| Zoom/Focus | Manual |
| Zoom Ratio | 1:1.2 |
| Up/Down Ratio | 9:1 |
| Digital Keystone Correction | Vertical: +/- 20 |
| Projection System | Polarized Beam Splitter optical system |
| Projection Lens | F1.65 - 1.81 / f0.89" - 1.06" |
| Lens Throw Ratio | 1.72 - 2.07:1 |
| Projection Lamp | 200W UHP |
| Scanning Frequency | H Sync: 15-100kHz, V Sync: 50-100Hz |
| Dot Clock | 140MHz |
| Color System | PAL/PAL-M/PAL-N/SECAM/NTSC/NTSC4.43 |
| Computer Compatibility | UXGA, WXGA, SXGA, XGA, SVGA, VGA, MAC |
| Sound Output | One-piece, 1-watt Mono |
| Voltage | 100-240V AC (auto Voltage) ; 50/60 Hz |
| BTU Rating | 836 |
| dB Rating | 32dB / 28dB (Normal/Eco) |
| Power Consumption | 245W/185W (Normal/Eco) |
| Dimensions (WxHxD) | 13.2" x 3.1" x 9.4" (not including Adjustable Feet) |
| Net Weight | 6.8lbs |
| User Maintenance | Clean air filters, replace lamp assembly |
| PC Input Terminals | D-Sub15 x 2 (1 switchable in/monitor out) • Audio x 1 (Stereo mini-jack : common) |
| Video Input Terminals | Composite Video (RCA x 1) • S-Video (Mini-DIN 4-pin) • R & L/mono audio (RCA x 2) • Component Video (D-Sub15 input w/optional cable) • Audio for Component Video (stereo mini-jack : common) |
| Output Terminals | D-Sub15 x 1 (switchable In/monitor out) • Variable Audio (stereo mini-jack) |
| Included Accessories | I/R Remote Control • 2 AA Batteries • Owner's Manual (CD-ROM & Quick Reference Guide) • VGA Cable • Lens Cap • PIN Code Label • AC Power Supply Cord |
| Optional Accessories | • POA-CA-COMPVGA - VGA/Component Video Cable • POA-RCKIT04 - Presentation Kit (Remote Control w/USB Infrared Receiver) • POA-CAC-VCL2 - Soft Carrying Bag • 610 334 9565 - Replacement Lamp |
| Service Port | Mini DIN 8-pin |
| Warranty | Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty |

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.



(2 inputs, one in/monitor out switchable)



Optional Presentation Kit with Remote and USB Infrared Receiver

POA-RCKIT04